



### APPLICATION

LED high-performance wallwashers with wide & narrow beam light distribution.

### PRODUCT DESCRIPTION

Wallwasher made of aluminium alloy, Aluminium and stainless steel.  
 Clear 5mm safety glass  
 Silicon rubber gasket  
 Swivel range 95°  
 Mounting bracket made of plastic.  
 Lens angle 8°- 25°- 45°- 60°- 10°x45°  
 Colour standard : Mat anodized  
 Optional RAL codes.  
 LED power supply unit  
 Input 110 – 240V AC 50 / 60 Hz  
 Power factor > 90% full load  
 DALI controllable (optional)  
 0-10V / 1-10V controllable (optional)  
 Safety class I  
 Protection class IP66  
 Impact strenght IK08  
 Operation temperature -25°C / +55°C  
 Wind catching area: 0,14 m<sup>2</sup>  
 Weight: 6,3 kg  
 EULUMDAT files available  
 Complies with European standards  
 EN 60598 and CE certificate.  
**CE** -- Conformity mark.

### LAMPS

Module connected wattage 48W  
 Luminaire connected wattage 60W  
 Ambient temperature t<sup>a</sup> max = 55 °C

### NW

Module designation 15L30320NC-36  
 Colour temperature 4000K  
 Colour rendering index R<sup>a</sup>>80  
 Module luminous flux 6960 lm  
 Luminaire luminous flux 5904 lm  
 Luminaire luminous efficiency 123 lm / W

### WW

Module designation 15L30320NC-36  
 Colour temperature 3000K  
 Colour rendering index R<sup>a</sup>>80  
 Module luminous flux 6720 lm  
 Luminaire luminous flux 5616 lm  
 Luminaire luminous efficiency 117 lm / W

**Standard colour temperature 4000K**  
**Also available with 3000K on request.**