

WALLWASHER VEGA 100CM 36W RGB-RGBA IP66 IK08 EN60598 (€



APPLICATION

LED high-performance wallwashers with wide & narrow beam light distribution.

PRODUCT DESCRIPTION

LED wall washing fixture with intelligent white and color light.

Fixture made of aluminium alloy, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Swivel range 95°

Mounting bracket made of plastic.

Lens angle 8°- 25°- 45°- 60°

Colour standard: Mat anodizied

optional RAL codes.

LED power supply unit

Input 110 - 240V AC 50 / 60 Hz

Power factor > 90% full load

DALI controllable, DMX 512 or

0-10V / 1-10V controllable.

Safety class I

Protection class IP66

Impact strenght IK08

Operation temperature -25°C / +55°C

Wind catching area: 0,14m2

Weight: 4,84 kg

info@bayled.com.tr

Complies with European standards

EN 60598 and CE certificate.

(*\infty* **-- Conformity mark.**

1000

LAMPS

Module connected wattage 36WLuminaire connected wattage 60WRated temperature $t^a = 25 \,^{\circ}C$ Ambient temperature $t^a = 35 \,^{\circ}C$ If the power is reduced, the max ambient temperature will increase. To min. $55 \,^{\circ}C$

FEATURES

Color-changing and high-quality white light from the same fixture. VEGA is an advanced approach to color mixing that enables high-quality intelligent color.

Multiple changes of LED lightscures combine

Multiple channels of LED lightsoures combine to produce a full spectrum of precisely controllable light, including millons of saturated colors, pastels and uniform white light with CRI of greater than 85 in 2700K – 4000K range.

DMX 512

Interface: Data Enabler (DMX/Bayled)

Adress method: Digital

Fixture Connections: male/female XLR

DALI - 0-10V

Interface: Controlable driver.
Control method: Analog with cable.
Fixture Connections: With cable

FIXTURE RUN LENGHTS

To calculate fixture run lenghts and total power consumption for your specific installation, please ask to company assistant.

BAYLED TEKNOLOJİ A.Ş. Ahi Evran Mah. 225. Cad. No:84 06935, Sincan ANKARA / TURKEY T: +90 312 395 76 35 F: +90 312 395 73 65 We reserve the right to change specifications without prior written notice. Edition: 03.05.2016 Current version under: www.bayled.com.tr Bayled is a Baytaş group brand.