



APPLICATION

LED high-performance wallwashers with wide & narrow beam light distribution.

PRODUCT DESCRIPTION

Wallwasher made of aluminium alloy,
Aluminium and stainless steel.
Clear 5mm safety glass
Silicon rubber gasket
Swivel range 95°
Mounting bracket made of plastic.
Lens angle 8°- 25°- 45°- 60°- 10°x45°
Colour standard : Mat anodized
optional RAL codes.
LED power supply unit
Input 110 – 240V AC 50 / 60 Hz
Power factor > 90% full load
DALI controllable (optional)
0-10V / 1-10V controllable (optional)
Safety class I
Protection class IP66
Impact strenght IK08
Operation temperature -25°C / +55°C
Wind catching area: 0,14 m²
Weight: 4,84 kg
EULUMDAT files available
Complies with European standards
EN 60598 and CE certificate.
CE -- Conformity mark.

LAMPS

Module connected wattage 36W
Luminaire connected wattage 60W
Ambient temperature t^a max = 55 °C

NW

Module designation 15L30320NC-36
Colour temperature 4000K
Colour rendering index R^a>80
Module luminous flux 5220 lm
Luminaire luminous flux 4428 lm
Luminaire luminous efficiency 123 lm / W

WW

Module designation 15L30320NC-36
Colour temperature 3000K
Colour rendering index R^a>80
Module luminous flux 5040 lm
Luminaire luminous flux 4212 lm
Luminaire luminous efficiency 117 lm / W

Standard colour temperature 4000K

Also available with 3000K on request.