



APPLICATION

LED high-performance wallwashers with Wide beam light distribution.

PRODUCT DESCRIPTION

Wallwasher made of aluminium extrusion, Aluminium and stainless steel.

Silicon rubber gasket

Swivel range 95°

Mounting bracket made of plastic.

LED chip angle 125° (without lens)

Colour standard : Mat anodized optional RAL codes.

LED power supply unit

Input 170 – 240V AC 50 / 60 Hz

Power factor > 90% full load

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Operation temperature -25°C / +55°C

Wind catching area: 0,06 m²

Weight: 0,75 kg

Complies with European standards

EN 60598 and CE certificate.

CE -- Conformity mark.

LAMPS

Module connected wattage 18W

Luminaire connected wattage 24W

Rated temperature t^a = 25 °C

Ambient temperature t^a max = 35 °C

If the power is reduced, the max ambient temperature will increase. To min. 55 °C

NW

Module designation 10L16325NC-33

Colour temperature 4000K

Colour rendering index R^a>80

Module luminous flux 2610 lm

Luminaire luminous flux 2214 lm

Luminaire luminous efficiency 123 lm / W

WW

Module designation 10L16325NC-33

Colour temperature 3000K

Colour rendering index R^a>80

Module luminous flux 2520 lm

Luminaire luminous flux 2106 lm

Luminaire luminous efficiency 117 lm / W

Standard colour temperature 4000K

Also available with 3000K on request.