



### APPLICATION

LED high-performance High-Bays with wide & narrow beam light distribution.

### PRODUCT DESCRIPTION

High-Bays made of aluminium die cast, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Mounting bracket made of steel with Electrostatic powder coating.

Lens angle 40° - 60° - 90°

Colour standard MT-X6-23

Optional RAL codes.

LED power supply unit

Input 100 – 305V AC 50 / 60 Hz

Power factor > 90% full load

6kV surge protection

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Impact strenght IK09

Operation temperature -25°C / +55°C

Wind catching area: 0,08 m<sup>2</sup>

Weight: 5,7 kg

EULUMDAT files available

Complies with European standards

EN 60598 and CE certificate.

CE -- Conformity mark.

### LAMPS

Module connected wattage 45W

Luminaire connected wattage 60W

Rated temperature t<sup>a</sup> = 25 °C

Ambient temperature t<sup>a</sup> max = 35 °C

If the power is reduced, the max ambient temperature will increase. To min. 55 °C

### NW

Module designation 15S163184NC-80

Colour temperature 4000K

Colour rendering index R<sup>a</sup>>80

Module luminous flux 6525 lm

Luminaire luminous flux 5535 lm

Luminaire luminous efficiency 123 lm / W

### WW

Module designation 15S163184NC-80

Colour temperature 3000K

Colour rendering index R<sup>a</sup>>80

Module luminous flux 6300 lm

Luminaire luminous flux 5265 lm

Luminaire luminous efficiency 117 lm / W

**Standard colour temperature 4000K**

**Also available with 3000K on request.**

### Accessories

Anti-Glare Diffusers

Viewing Angle



0° / 45° / 65°

**BAYLED TEKNOLOJİ A.Ş.**

**Ahi Evran Mah. 225. Cad. No:84**

**06935, Sincan ANKARA / TURKEY**

**T: +90 312 395 76 35**

**F: +90 312 395 73 65**

**info@bayled.com.tr**

Bayled All right reserved

We reserve the right to change specifications without prior written notice.

Edition: 03.05.2016

Current version under:

[www.bayled.com.tr](http://www.bayled.com.tr)

Bayled is a Baytaş group brand.