



### APPLICATION

LED high-performance Floodlights with wide & narrow beam light distribution.

### PRODUCT DESCRIPTION

Movable Head

Floodlights made of aluminium die cast, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Mounting bracket made of steel with electrostatic powder coating.

Lens angle 40°- 60°- 90° - 30°x96°

Colour standard MT-X6-23 optional RAL codes.

LED power supply unit

Input 100 – 305V AC 50 / 60 Hz

Power factor > 90% full load

6kV surge protection

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Impact strenght IK09

Operation temperature -25°C / +55°C

Wind catching area: 0,24 m<sup>2</sup>

Weight: 22,3 kg

EULUMDAT files available

Complies with European standards

EN 60598 and CE certificate.

**CE** -- Conformity mark.

### LAMPS

Module connected wattage 270W

Luminaire connected wattage 300W

Ambient temperature t<sup>a</sup> max = 55 °C

### NW

Module designation 10S109344NC-384

Colour temperature 4000K

Colour rendering index R<sup>a</sup>>80

Module luminous flux 39150 lm

Luminaire luminous flux 33210 lm

Luminaire luminous efficiency 123 lm / W

### WW

Module designation 10S109344NC-384

Colour temperature 3000K

Colour rendering index R<sup>a</sup>>80

Module luminous flux 37800 lm

Luminaire luminous flux 31590 lm

Luminaire luminous efficiency 117 lm / W

**Standard colour temperature 4000K**

**Also available with 3000K on request.**

### BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84

06935, Sincan ANKARA / TURKEY

T: +90 312 395 76 35

F: +90 312 395 73 65

info@bayled.com.tr

Bayled All right reserved

We reserve the right to change specifications without prior written notice.

Edition: 03.05.2016

Current version under:

[www.bayled.com.tr](http://www.bayled.com.tr)

Bayled is a Baytaş group brand.