



APPLICATION

LED high-performance High-Bays with wide & narrow beam light distribution.

PRODUCT DESCRIPTION

High-Bays made of aluminium alloy, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Mounting bracket made of steel with electrostatic powder coating.

Lens angle 40° - 60° - 90° - 30°x50°

Colour standard MT-X6-23

optional RAL codes.

LED power supply unit

Input 100 – 305V AC 50 / 60 Hz

Power factor > 90% full load

6kV surge protection

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Impact strenght IK09

Operation temperature -25°C / +55°C

Wind catching area: 0,22m²

Weight: 28,4 kg

EULUMDAT files available

Complies with European standards

EN 60598 and CE certificate.

CE -- Conformity mark.

LAMPS

Module connected wattage 360W

Luminaire connected wattage 380W

Ambient temperature t^a max = 55°C

NW

Module designation 15L115330NC-512

Colour temperature 4000K

Colour rendering index R^a>80

Module luminous flux 56000 lm

Luminaire luminous flux 42840 lm

Luminaire luminous efficiency 115 lm / W

WW

Module designation 15L115330NC-512

Colour temperature 3000K

Colour rendering index R^a>80

Module luminous flux 55200 lm

Luminaire luminous flux 41400 lm

Luminaire luminous efficiency 110 lm / W

Standard colour temperature 4000K

Also available with 3000K on request.

BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84

06935, Sincan ANKARA / TURKEY

T: +90 312 395 76 35

F: +90 312 395 73 65

info@bayled.com.tr

Bayled All right reserved

We reserve the right to change specifications without prior written notice.

Edition: 03.05.2016

Current version under:

www.bayled.com.tr

Bayled is a Baytaş group brand.