



### APPLICATION

HIT high-performance decorative lights  
With wide beam light distribution

### PRODUCT DESCRIPTION

Body pole manufactured from cast aluminium  
Diffuser 5mm polycarbon glass  
Silicon rubber gasket  
Mounting detail anchor system  
All decorative parts, Base and Bracket  
manufactured cast aluminium  
All RAL Codes or  
Special architectural paints  
Ballast Magnetic (Standart) / Electronic  
High pressure electrical system  
Input 170 – 240V AC 50 / 60 Hz  
Power factor > 90% full load  
Safety class II  
Protection class IP65  
Operation temperature -25°C / +55°C  
EULUMDAT files available  
Complies with European standards  
EN 60598 and CE certificate.  
CE -- Conformity mark.

### LAMPS

Module connected wattage 70W  
Luminaire connected wattage 100W  
Ambient temperature  $t^a$  max = 55 °C

### NW

Colour temperature 4000K  
Colour rendering index  $R^a > 80$   
Luminaire luminous flux 6510 lm  
Luminaire luminous efficiency 93 lm / W

### WW

Colour temperature 3000K  
Colour rendering index  $R^a > 80$   
Luminaire luminous flux 6090 lm  
Luminaire luminous efficiency 87 lm / W

**Standard colour temperature 4000K**

**Also available with 3000K on request.**