27/01/2019

STREET LIGHT B-LIGHT 140W IP66 IK08 EN60598 CE







APPLICATION

LED high-performance street lights with Wide & Asymmetric Beam light distribution.

PRODUCT DESCRIPTION

Street lights made of aluminium die cast, Aluminium and stainless steel.
Clear 5mm safety glass
Silicon rubber gasket
Swivel range with bracket 0° - 80°
Mounting bracket made of steel & alumin. with electrostatic powder coating.
Lens angle asimetric
Colour standard MT-X6-23
Optional RAL codes.
LED power supply unit
Input 100 – 305V AC 50 / 60 Hz
Power factor > 90% full load
Standard 6kV surge protection
10kV surge protection (optional)
DALI controllable (optional)
0-10V / 1-10V controllable (optional)
Safety class I
Protection class IP66
Impact strenght IK08
Operation temperature -25°C / +55°C
Wind catching area: 0,18 m^2
Weight: 11,34 kg
EULUMDAT files available
Complies with European standards EN 60598 and CE certificate.
CE -- Conformity mark.

LAMPS

Module connected wattage	140W
Luminaire connected wattage	150W
Rated temperature	t^a = 25 °C
Ambient temperature	t^a max = 35 °C

If the power is reduced, the max ambient temperature will increase. To min. 55 °C

NW

Module designation	15S212240NC-64
Colour temperature	4000K
Colour rendering index	R^a>80
Module luminous flux	21000 lm
Luminaire luminous flux	16660 lm
Luminaire luminous efficiency	119 lm / W

WW

Module designation	15S212240NC-64
Colour temperature	3000K
Colour rendering index	R^a>80
Module luminous flux	20700 lm
Luminaire luminous flux	16100 lm
Luminaire luminous efficiency	115 lm / W

Standard colour temperature 4000K
Also available with 3000K on request.

Accessories

Montage Bracket

20° / 40° / 60° / 80°

BAYLED TEKNOLOJİ A.Ş.
Ahi Evran Mah. 225. Cad. No:84
06935, Sincan ANKARA / TURKEY
T: +90 312 395 76 35
F: +90 312 395 73 65
info@bayled.com.tr

Bayled All right reserved

We reserve the right to change specifications without prior written notice.
Edition: 03.05.2016
Current version under:
www.bayled.com.tr
Bayled is a Baytaş group brand.