



## PRODUCT DATA

## General Information

Number of light source	192 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	40°- 60°- 90°
Light source colour	3000K-4000K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Multi lens
Control interface	On/Off
Connection	-
Cable	3x1,5 mm <sup>2</sup>
Protection class IEC	Safety class II
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	60-56-140-XX-X (XX: Lens angle, X: Led colour)

## Operating and Electrical

Input Voltage	90-264 V AC
Input frequency	50 to 60 Hz
Inrush current	636 mA
Power factor (min.)	0.92

## Control and Dimming

Dimmable(optional)	1-10V - DALI
DMX	-

## Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Glass (5mm)
Fixation material	Stainless steel
Mounting device	-
Effective projected area	4,48m <sup>2</sup> - 2,88m <sup>2</sup>
Colour	Grey
Dimensions (height x width x depth)	7000(4500) x 640 x 1152 mm

## Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK08
Surge protection (common/differential)	6 KV/4KV (optional)

## Initial Performance (IEC Compliant)

Module luminous flux	22104 lm (4000K) / 21005 lm (3000K)
Luminaire luminous flux	20777 lm (4000K) / 19745 lm (3000K)
LED luminaire efficiency	148 lm (4000K) / 140 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	>70
Rated LED power	127W
Rated luminaire power	140W

## Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	Variable

## Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

