

# EXEGI-3 240 315W






HIGH-LOW BAY LINEAR

IP66

IK10



EN60598 CE



## PRODUCT DATA

### General Information

Number of light source	1152 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	120°(without lens)
Light source colour	6500K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Diffuser
Control interface	On/Off
Connection	-
Cable	3x1,5 mm <sup>2</sup>
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	90-03-240-315-1152-X (XX: Lens angle, X: Led colour)

### Operating and Electrical

Input Voltage	198-264 V AC
Input frequency	50 to 60 Hz
Inrush current	1432 mA
Power factor (min.)	0.92

### Control and Dimming

Dimmable(optional)	1-10V - DALI
DMX	-

### Mechanical and Housing

Housing material	Plastic
Gasket	Silicone
Optic material	-
Optical cover / lens material	PMMA
Fixation material	Plastic and stainless steel mounting bracket
Mounting device	-
Effective projected area	0,64m <sup>2</sup>
Colour	Grey
Dimensions (height x width x depth)	267 x 2410 x 147 mm

### Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK10
Surge protection (common/differential)	2 KV/1KV

### Initial Performance (IEC Compliant)

Module luminous flux	53454 lm (6500K)
Luminaire luminous flux	44901 lm (6500K)
LED luminaire efficiency	143 lm (6500K)
Colour Temperature	6500K
	4000K / 3000K also available up on request.
Colour rendering index	>70
Rated LED power	286W
Rated luminaire power	315W

### Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	13,36 kg

**Fixture Run Length** To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

#### BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84 06935, Sincan ANKARA / TURKEY  
T: +90 312 395 76 35 | F: +90 312 395 73 65 | sales@bayled.com.tr

Bayled is a Baytaş group brand.

Scan the QR Code to go to the product web page.



We reserve the right to change specifications without prior written notice.

Current version under: [www.bayled.eu](http://www.bayled.eu)