


PAR 56**18W****BAYLED®****UNDERWATER****IP68****EN60598 CE****PAR 56****PRODUCT DATA****General Information**

Number of light source	18 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	8° - 25° - 45° - 60°
Light source colour	3000K-4000K, RGB
Number of gear unit	1 unit
Driver / power unit	PS (Constant voltage)
Driver included	No
Optical cover / lens type	Single lens
Control interface	On/Off
Connection	-
Cable	2x0,75 mm ²
Protection class IEC	Safety class II
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	30-03-24-18-PAR56-XX-X (XX: Lens angle, X: Led colour)

Operating and Electrical

Input Voltage	24 - 36 V DC
Input frequency	-
Inrush current	350 mA
Power factor (min.)	0.92

Control and Dimming

Dimmable(optional)	1-10V - DALI
DMX	-

Mechanical and Housing

Housing material	Stainless steel
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	PMMA
Fixation material	Stainless steel mounting bracket
Mounting device	-
Effective projected area	0,03m ²
Colour	Grey
Dimensions (height x width x depth)	179 x 179 x 70 mm

Approval and Application

Ingress protection code	IP68
Mech. impact protection code	-
Surge protection (common/differential)	-

Initial Performance (IEC Compliant)

Module luminous flux	2774 lm (4000K) / 2636 lm (3000K)
Luminaire luminous flux	2607 lm (4000K) / 2478 lm (3000K)
LED luminaire efficiency	145 lm (4000K) / 138 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	>70
Rated LED power	16W
Rated luminaire power	18W

Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	0,78 kg

Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84 06935, Sincan ANKARA / TURKEY
T: +90 312 395 76 35 | F: +90 312 395 73 65 | sales@bayled.com.tr

Bayled is a Baytaş group brand.

Scan the
QR Code
to go to
the product
web page.



We reserve the right to change specifications without prior written notice.

Current version under: www.bayled.eu