



PRODUCT DATA

Application	Escape Sign, Anti-Panic Lightning, Escape route lightning, Hazardous Area Lightning
Mounting	Direct mounting to Wall & ceiling. Recessed mounting is available by accessory
Type	Manuel Test, Self Test, DALI, Wireless
Mode	Selectable maintained/non-maintained
Emergency Duration	Selectable 1/3 hours
Viewing Distance	23m. Single sided
Light Source	LED module, 12 mid power LEDs, 6500K, CRI>80
Battery	3.6V High temperature battery block, Ni-Cd/Ni-MH
Wiring	Up to 2*2,25mm ² quick fit terminal block
Cable Entry	Four easy breakable entry holes back, rear & top parts
Power Supply	230 Volt, 50/60Hz, max 0,05A, max 5W
Protection	IP65
Temperature Range	5-40°C
Electrical Class	Class II (no earth wiring required)
Material	White polycarbonate housing

PRODUCT CODE

Code	Type	Battery	Light Output & Duration
ELGS-SM8E	ECO	Ni-Cd	1 hour, 185Lm or 3 hours, 77Lm
ELGS-SM15E			1 hour, 232Lm or 3 hours, 145Lm
ELGS-SM15E-MH		Ni-MH	1 hour, 232Lm or 3 hours, 145Lm
ELGS-SM22E-MH			1 hour, 278Lm or 3 hours, 212Lm
ELGS-SM8-ST	SELF TEST	Ni-Cd	1 hour, 185Lm or 3 hours, 77Lm
ELGS-SM15-ST			1 hour, 232Lm or 3 hours, 145Lm
ELGS-SM15-ST-MH		Ni-MH	1 hour, 232Lm or 3 hours, 145Lm
ELGS-SM22-ST-MH			1 hour, 278Lm or 3 hours, 212Lm
ELGS-SM22-DALI	DALI	Ni-MH	3 hour, 135Lm
ELGS-1224	CENTRAL	24V AC/DC	
ELGS-12230		230V AC/DC	
ELGS-PAD-S	Changeable sign PAD (inside the cover)		
ELGS-PAD-W	Changeable white PAD for opal lightning effect (inside the cover)		
ELGS-ANK	Recessed mounting box		

VIEWING AREA

