



PRODUCT DATA

Application	Anti-Panic Lighting, Escape Route Lighting, Hazardous Area Lighting
Mounting	Direct mounting to ceiling., recessed mount (ERL)
Type	Manuel Test, Self Test, DALI, Wireless
Mode	Non-maintained
Emergency Duration	EL 1/3 hours, SQL 1/3/5/8 hours
Light Source	Power LED, 6500K, CRI>80
Battery	3.6V High temperature battery block, Ni-Cd/Ni-MH
Wiring	Up to 2x2,25mm ² quick fit terminal block
Cable Entry	Top side
Power Supply	230 Volt, 50/60Hz, max 0,03A, max 5W
Protection	IP30
Temperature Range	5-45°C
Electrical Class	Class II (no earth wiring required)
Material	White polycarbonate housing

PRODUCT CODE

Code	Mounting	Type	Duration	Light Source	
ERLR-NM111	Recessed	ECO	1 hours	150 Lumen	
ERLR-NM311			3 hours		
ERLR-NM111-ST		SELF TEST	1 hours		
ERLR-NM311-ST			3 hours		
ERLR-NM311-DALI		DALI			
ERLR-24		CENTRAL			
ERLR-230			-		
ERLS-NM111		Surface	ECO		1 hours
ERLS-NM311					3 hours
ERLS-NM111-ST	SELF TEST		1 hours		
ERLS-NM311-ST			3 hours		
ERLS-NM311-DALI	DALI				
ERLS-24	CENTRAL				
ERLS-230			-		

