



PRODUCT DATA

Application	Anti-Panic Lighting, Escape Route Lighting, Hazardous Area Lighting
Mounting	Direct mounting to ceiling
Type	Manuel Test, Self Test, DALI, Wireless
Mode	Non-maintained
Emergency Duration	EL 1/3 hours, SQL 1/3/5/8 hours
Light Source	Power LED, 6500K, CRI>80
Battery	3.6V High temperature battery block, Ni-Cd/Ni-MH
Wiring	Up to 2x2,25mm ² quick fit terminal block
Cable Entry	Top side
Power Supply	230 Volt, 50/60Hz, max 0,03A, max 5W
Protection	IP40
Temperature Range	5-45°C
Electrical Class	Class II (no earth wiring required)
Material	White polycarbonate housing

PRODUCT CODE

Code	Type	Duration	Light Output
SQL-NM11E	ECO	1 hours	150 Lumen
SQL-NM31E		3 hours	150 Lumen
SQL-NM51E		5 hours	150 Lumen
SQL-NM81E		8 hours	95 Lumen
SQL-NM11H		1 hours	188 Lumen
SQL-NM31H		3 hours	188 Lumen
SQL-NM11-ST	SELF TEST	1 hours	150 Lumen
SQL-NM31-ST		3 hours	150 Lumen
SQL-NM11H-ST		1 hours	188 Lumen
SQL-NM31H-ST		3 hours	188 Lumen
SQL-NM31-DALI	150 Lumen		
SQL-NM31H-DALI	DALI	188 Lumen	
SQL-24	CENTRAL	-	150 Lumen
SQL-230			150 Lumen

