



PRODUCT DATA

General Information

Number of light source	18 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	8° - 25° - 45° - 60°
Light source colour	3000K-4000K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Single lens
Control interface	On/Off
Connection	-
Cable	3x0,75 mm ²
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	15-03-25-18-XX-X (XX: Lens angle, X: Led colour)

Operating and Electrical

Input Voltage	88-264 V AC
Input frequency	50 to 60 Hz
Inrush current	114 mA
Power factor (min.)	0.92

Control and Dimming

Dimmable(optional)	1-10V - DALI
DMX	-

Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Glass (5mm)
Fixation material	Aluminium and stainless steel mounting bracket
Mounting device	Black color recess box made of plastic
Effective projected area	0,05m ²
Colour	Grey
Dimensions (height x width x depth)	232 x 198 x 198 mm

Approval and Application

Ingress protection code	IP67
Mech. impact protection code	IK09
Surge protection (common/differential)	-

Initial Performance (IEC Compliant)

Module luminous flux	3077 lm (4000K) / 2924 lm (3000K)
Luminaire luminous flux	2769 lm (4000K) / 2631 lm (3000K)
LED luminaire efficiency	110 lm (4000K) / 105 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	>70
Rated LED power	23W
Rated luminaire power	25W

Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	2,5 kg

Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

