



## PRODUCT DATA

## General Information

Number of light source	18 pcs
LED module	High Power LED's on alu-PCB
Light distribution	8°- 25°- 45° - 60°
Light source colour	RGB
Number of gear unit	1 unit
Driver / power unit	PS (Constant voltage)
Driver included	Yes
Optical cover / lens type	Single lens
Control interface	DMX
Connection	-
Cable	4x0,75 mm <sup>2</sup>
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	N/A
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	20-03-25-18-XX-H-RGB-DMX (XX: Lens angle, X: Led colour)

## Operating and Electrical

Input Voltage	24 V DC
Input frequency	-
Inrush current	350 mA x each channel
Power factor (min.)	0.92

## Control and Dimming

Dimmable(optional)	-
DMX	DMX512

## Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	PMMA
Fixation material	Stainless steel and plastic mounting bracket
Mounting device	-
Effective projected area	0,07m <sup>2</sup>
Colour	Grey
Dimensions (height x width x depth)	393 x 179 x 179 mm

## Approval and Application

Ingress protection code	IP66
Mech. impact protection code	-
Surge protection (common/differential)	-

## Initial Performance (IEC Compliant)

Module luminous flux	1278 lm (RGB)
Luminaire luminous flux	1176 lm (RGB)
LED luminaire efficiency	47 lm (RGB)
Colour Temperature	RGB
Colour rendering index	>80
Rated LED power	23W
Rated luminaire power	25W

## Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	1,5 kg

## Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

