

SIRUS M 200W




FLOODLIGHT

IP66

IK09



EN60598 CE



PRODUCT DATA

General Information

Number of light source	180 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	15°-40°-60°-90°-30°x96°
Light source colour	3000K-4000K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Multi lens
Control interface	On/Off
Connection	-
Cable	2x1,5 mm ²
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Symmetric-asymmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	45-07-200-24-180-XX-X (XX: Lens angle, X: Led colour)

Operating and Electrical

Input Voltage	24 V DC
Input frequency	-
Inrush current	10000 mA
Power factor (min.)	0.92

Control and Dimming

Dimmable(optional)	1-10V
DMX	-

Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Glass (5mm)
Fixation material	Stainless steel
Mounting device	-
Effective projected area	0,21m ²
Colour	Grey
Dimensions (height x width x depth)	540 x 391 x 56 mm

Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK09
Surge protection (common/differential)	-

Initial Performance (IEC Compliant)

Module luminous flux	28682 lm (4000K) / 27257 lm (3000K)
Luminaire luminous flux	26388 lm (4000K) / 25077 lm (3000K)
LED luminaire efficiency	132 lm (4000K) / 125 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	≥70
Rated LED power	182W
Rated luminaire power	200W

Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	10 kg

Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

