

# ROON 30W BLUE




FLOODLIGHT

IP66

IK07



EN60598 CE



## PRODUCT DATA

### General Information

|                            |   |
|----------------------------|---|
| Number of light source     | 112 pcs   |
| LED module                 | Mid Power LED's on alu-PCB                        |
| Light distribution         | 30°   |
| Light source colour        | BLUE  |
| Number of gear unit        | 1 unit  |
| Driver / power unit        | PS (Constant current)                             |
| Driver included            | Yes   |
| Optical cover / lens type  | Multi lens  |
| Control interface          | On/Off  |
| Connection                 | -   |
| Cable                      | 3x0,75 mm <sup>2</sup>                            |
| Protection class IEC       | Safety class I                                    |
| CE mark                    | CE mark   |
| ENEC mark                  | -   |
| Warranty period            | 5 years   |
| Optic type                 | Symmetric   |
| EU RoHS compliant          | Yes   |
| Light source engine type   | LED   |
| LDT / IES photometric file | Available   |
| Life span                  | Estimated average 50.000 hours                    |
| MacAdams                   | CCT tolerance within a 3 step MacAdams ellipse    |
| Product code               | 45-29-30-112-30-B (XX: Lens angle, X: Led colour) |

### Operating and Electrical

|                     |              |
|---------------------|--------------|
| Input Voltage       | 100-305 V AC |
| Input frequency     | 50 to 60 Hz  |
| Inrush current      | 136 mA       |
| Power factor (min.) | 0.92         |

### Control and Dimming

|                    |              |
|--------------------|--------------|
| Dimmable(optional) | 1-10V - DALI |
| DMX                | -            |

### Mechanical and Housing

|                                     |                    |
|-------------------------------------|--------------------|
| Housing material                    | Aluminium die-cast |
| Gasket                              | Silicone           |
| Optic material                      | PMMA               |
| Optical cover / lens material       | Glass (5mm)        |
| Fixation material                   | Stainless steel    |
| Mounting device                     | -                  |
| Effective projected area            | 0,07m <sup>2</sup> |
| Colour                              | Grey               |
| Dimensions (height x width x depth) | 300 x 230 x 78 mm  |

### Approval and Application

|  |                              |
|--|------------------------------|
| Ingress protection code                | IP66                         |
| Mech. impact protection code           | IK07                         |
| Surge protection (common/differential) | 6 KV/4KV (10KV/6KV optional) |

### Initial Performance (IEC Compliant)

|                          |   |
|--------------------------|---|
| Module luminous flux     | 832 lm (BLUE)                           |
| Luminaire luminous flux  | 749 lm (BLUE)                           |
| LED luminaire efficiency | 25 lm (BLUE)                            |
| Colour Temperature       | BLUE                                    |
|                          | RED-GREEN also available up on request. |
| Colour rendering index   | ≥70                                     |
| Rated LED power          | 27W                                     |
| Rated luminaire power    | 30W                                     |

### Application Conditions

|                           |                |
|---------------------------|----------------|
| Ambient temperature range | -25°C to +55°C |
| Maximum dimming level     | -              |
| Net weight (piece)        | 4,3 kg         |

### Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

#### BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84 06935, Sincan ANKARA / TURKEY  
T: +90 312 395 76 35 | F: +90 312 395 73 65 | sales@bayled.com.tr

Bayled is a Baytaş group brand.

Scan the QR Code to go to the product web page.



We reserve the right to change specifications without prior written notice.

Current version under: [www.bayled.eu](http://www.bayled.eu)