



Purchase Order Table

CODE	MODULE POWER	LUMINAIRE POWER	MODULE LUMINOUS FLUX	LUMINAIRE LUMINOUS FLUX	COLOR TEMPERATURE
01-02-35-12-XX-X	11W	12W	1778lm - 1871lm	1671lm - 1758lm	3000K-4000K
01-02-35-24-XX-X	22W	24W	3555lm - 3741lm	3342lm - 3517lm	3000K-4000K
01-02-70-24-XX-X	22W	24W	3555lm - 3741lm	3342lm - 3517lm	3000K-4000K
01-02-70-48-XX-X	44W	48W	7111lm - 7483lm	6684lm - 7034lm	3000K-4000K
01-02-100-36-XX-X	33W	36W	5333lm - 5612lm	4879lm - 5239lm	3000K-4000K
01-02-100-72-XX-X	66W	72W	10666lm - 11224lm	8733lm - 9377lm	3000K-4000K
01-02-130-48-XX-X	44W	48W	7111lm - 7483lm	6684lm - 7034lm	3000K-4000K
01-02-130-96-XX-X	87W	96W	14222lm - 14965lm	13369lm - 14068lm	3000K-4000K

XX : Lens Angle, X : Led Color
Standard color temperature 4000K, also available with 6500K on request.

USED POWER SUPPLY BRANDS








USED LED BRANDS







VEGA

EN 60598 | IK08 | IP66 | CE



Photometric Curves



Technical Specifications

Wallwasher made of aluminium extrusion,	0-10V / 1-10V controllable (optional)
Clear 5mm safety glass	Safety class I
Silicon rubber gasket	Protection class IP66
Swivel range 95°	Impact strength IK08
Mounting bracket made of plastic.	Operation temperature -25°C / +55°C
Lens angle 8°- 25°- 45°- 60° - 10°x45°	Wind catching area: 0,14m ²
Color standard mat anodized,	Weight: 35,5cm: 2kg / 68cm: 3.53kg
Input 198 - 264V AC 50 / 60 Hz	Weight: 100cm: 4.84kg / 132,5cm: 6.3kg
Power factor (min.) 0.92	EULUMDAT files available
Mono Color (Standard)	Complies with European standards
DALI controllable (optional)	EN 60598 and CE certificate

CCT tolerance within a 3 step MacAdams ellipse and LM80 compliant

Lifetime 50.000 working hours at least



Scan QR Code to get all technical documents and the other updated files for this product.

