

MULTILITE

Specifications

Application Escape Sign

Mounting Direct mounting to wall & ceiling. Suspended, recessed &

flag mounting are available by accessories

Manual Test, Self Test, DALI, Wireless Type Selectable maintained/non-maintained Mode

Emergency Duration Selectable 1/2/3/8 hours

Viewing Distance 23m, 30m. Single & double sided

Light Source LED module, 20 mid power leds, 6500K, CRI>80 Battery 3.6 Volt High temperature battery block, Ni-Cd/ Ni-MH

Wiring Up to 2x2,5 mm² quick fit terminal block

Cable Entry Two easy breakable entry holes rear & upper part

Power Supply 230 Volt, 50/60Hz, max 0,03A, max 5W


IP40 Protection Temperature Range 5-40°C

Electrical Class Class II (no earth wiring required) Material White polycarbonate housing





Dimensions (mm)



Ordering Details

Code	Function	Descrip tion
MTL-SM23E MTL-SM23ST MTL-SM23ST-LF MTL-SM23DALI	VD 23m	Standard type, Ni-Cd battery, 23m viewing distance, with sign pad Self-test type, Ni-Cd battery, 23m viewing distance, with sign pad Self-test type, Li-FePO4 battery, 23m viewing distance, with sign pad DALI type, Ni-MH battery, 23m viewing distance, with sign pad
MTL-SM30E MTL-SM30ST MTL-SM30ST-LF MTL-SM30DALI	VD 30m	Standard type, Ni-Cd battery, 30m viewing distance, with sign pad Self-test type, Ni-Cd battery, 30m viewing distance, with sign pad Self-test type, Li-FePO4 battery, 30m viewing distance, with sign pad DALI type, Ni-MH battery, 30m viewing distance, with sign pad
MTL-SSWR 2M MTL-REC MTL-FLAG	Mounting Accessories (spare part)	Suspended type hanging set (2m) Recessed mounting set Flag mounting set
MTL-23-LFT MTL-23-RGT MTL-23-UP MTL-23-DWN MTL-23-pad	Legends 23m (spare part)	23m left type sign 23m right type sign 23m up type sign 23m down type sign 23m white pad for single side use
MTL-30-LFT MTL-30-RGT MTL-30-UP MTL-30-DWN MTL-23-pad	Legends 30m (spare part)	30m left type sign 30m right type sign 30m up type sign 30m down type sign 30m down type sign 30m white pad for single side use
MTL-CLP-Set	Legend fixing clips set (spare part)	

Viewing Distance

