


SINGLE HEAD

CODE	MODULE POWER	LUMINAIRE POWER	MODULE LUMINOUS FLUX	LUMINAIRE LUMINOUS FLUX	COLOR TEMPERATURE
20-012-018-018-XX-X	16W	18W	2273lm - 2392lm	2046lm - 2152lm	3000K-4000K
20-012-018-025-XX-X	23W	25W	2924lm - 3077lm	2631lm - 2769lm	3000K-4000K


DOUBLE HEAD

CODE	MODULE POWER	LUMINAIRE POWER	MODULE LUMINOUS FLUX	LUMINAIRE LUMINOUS FLUX	COLOR TEMPERATURE
20-012-036-036-XX-X	33W	36W	4475lm - 4712lm	4068lm - 4284lm	3000K-4000K
20-012-036-050-XX-X	46W	50W	6215lm - 6545lm	5650lm - 5950lm	3000K-4000K


XX : Lens Angle, X : Led Color
Standard color temperature 4000K, also available with 6500K on request.

BLAZE ROUND

EN 60598 | IK09 | IP67 | CE



Photometric Curves



Technical Specifications

Sconce made of aluminium die cast & extrusion	Mono color (Standard)
Aluminium and stainless steel	DALI controllable (Optional)(External)
Clear 5mm safety glass	0-10V / 1-10V controllable (Optional) (External)
Silicon base seal gasket	Safety Class I
Mounting bracket made of steel	Protection Class IP67
Electrostatic powder coating	Impact strength IK09
Lens angle 8°-25°-45°-60°	Operation temperature -25°C / +55°C
Color standard 7040, optional RAL codes	Weight: Single Head: 3 kg , Double Head: 4,8 kg
Input 90 -264V AC 50 / 60 Hz	Complies with European standards
Power factor (min.) 0.92	EN 60598 and CE certificate

CCT tolerance within a 3 step MacAdams ellipse and LM80 compliant

Lifetime 50.000 working hours at least



Scan QR Code to get all technical documents and the other updated files for this product.

