

# ANKA SQUARE 3W




## SURFACE MOUNT LUMINAIRES

IP67

IK07



EN60598 CE



## PRODUCT DATA

### General Information

Number of light source	1 pcs
LED module	High Power LED's on alu-PCB
Light distribution	8°- 15°- 25°- 36° - 60°
Light source colour	3000K-4000K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Single lens
Control interface	On/Off
Connection	-
Cable	3x0,75 mm <sup>2</sup>
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Symmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	20-05-01-03-XX-X (XX: Lens angle, X: Led colour)

### Operating and Electrical

Input Voltage	100 - 240 V AC
Input frequency	50 to 60 Hz
Inrush current	29 mA
Power factor (min.)	0.92

### Control and Dimming

Dimmable(optional)	-
DMX	-

### Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Glass (5mm)
Fixation material	Aluminium and stainless steel mounting bracket
Mounting device	-
Effective projected area	0,01m <sup>2</sup>
Colour	Grey
Dimensions (height x width x depth)	115 x 116 x 131 mm

### Approval and Application

Ingress protection code	IP67
Mech. impact protection code	IK07
Surge protection (common/differential)	-

### Initial Performance (IEC Compliant)

Module luminous flux	297 lm (4000K) / 310 lm (3000K)
Luminaire luminous flux	270 lm (4000K) / 282 lm (3000K)
LED luminaire efficiency	90 lm (4000K) / 94 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	≥70
Rated LED power	3W
Rated luminaire power	3W

### Application Conditions

Ambient temperature range	-20°C to +50°C
Maximum dimming level	-
Net weight (piece)	1,05 kg

### Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84 06935, Sincan ANKARA / TURKEY  
T: +90 312 395 76 35 | F: +90 312 395 73 65 | sales@bayled.com.tr

Bayled is a Baytaş group brand.

Scan the  
QR Code  
to go to  
the product  
web page.



We reserve the right to change specifications without prior written notice.  
Current version under: [www.bayled.eu](http://www.bayled.eu)