

SIRUS L RGB 210W




FLOODLIGHT

IP66

IK08



EN60598 CE



PRODUCT DATA

General Information

Number of light source	108 pcs
LED module	Mid Power LED's on alu-PCB
Light distribution	10°- 30°- 60°-90°-ASYM
Light source colour	RGB
Number of gear unit	1 unit
Driver / power unit	PS (Constant voltage)
Driver included	Yes
Optical cover / lens type	Multi lens
Control interface	DMX
Connection	-
Cable	3x1,5 mm ² (Power) + 3x0,5 mm ² (DMX)
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Symmetric - asymmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	-
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	45-01-210-108-XX-RGB (XX: Lens angle, X: Led colour)

Operating and Electrical

Input Voltage	85-265 V AC
Input frequency	50 to 60 Hz
Inrush current	955 mA
Power factor (min.)	0.92

Control and Dimming

Dimmable(optional)	-
DMX	DMX512

Mechanical and Housing

Housing material	Aluminium die-cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Glass (5mm)
Fixation material	Stainless steel
Mounting device	-
Effective projected area	0,30m ²
Colour	Grey
Dimensions (height x width x depth)	606 x 490 x 70 mm

Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK08
Surge protection (common/differential)	6 KV/4KV (optional)

Initial Performance (IEC Compliant)

Module luminous flux	11016 lm (RGB)
Luminaire luminous flux	10135 lm (RGB)
LED luminaire efficiency	48 lm (RGB)
Colour Temperature	RGB
Colour rendering index	≥70
Rated LED power	191W
Rated luminaire power	210W

Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	14.86 kg

Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

