



APPLICATION

LED high-performance High-Bays with wide & narrow beam light distribution.

PRODUCT DESCRIPTION

High-Bays made of aluminium die cast, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Mounting bracket made of steel with Electrostatic powder coating.

Lens angle 15° - 40° - 60° - 90° - 30°x96°

Colour standard MT-X6-23

Optional RAL codes.

LED power supply unit

Input 100 – 305V AC 50 / 60 Hz

Power factor > 90% full load

6kV surge protection

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Impact strenght IK09

Operation temperature -25°C / +55°C

Wind catching area: 0,32 m²

Weight: 23 kg

EULUMDAT files available

Complies with European standards

EN 60598 and CE certificate.

CE -- Conformity mark.

LAMPS

Module connected wattage 460W

Luminaire connected wattage 500W

Ambient temperature t^a max = 55 °C

NW

Module designation 10S109344NC-512

Colour temperature 4000K

Colour rendering index R^a>80

Module luminous flux 69812 lm

Luminaire luminous flux 65623 lm

Luminaire luminous efficiency 143 lm / W

WW

Module designation 10S109344NC-512

Colour temperature 3000K

Colour rendering index R^a>80

Module luminous flux 66343 lm

Luminaire luminous flux 62362 lm

Luminaire luminous efficiency 136 lm / W

Standard colour temperature 4000K

Also available with 3000K on request.

BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84

06935, Sincan ANKARA / TURKEY

T: +90 312 395 76 35

F: +90 312 395 73 65

info@bayled.com.tr

Bayled All right reserved

We reserve the right to change specifications without prior written notice.

Edition: 03.05.2016

Current version under:

www.bayled.com.tr

Bayled is a Baytaş group brand.