



APPLICATION

LED high-performance High-Bays with wide & narrow beam light distribution.

PRODUCT DESCRIPTION

High-Bays made of aluminium die cast, Aluminium and stainless steel.

Clear 5mm safety glass

Silicon rubber gasket

Mounting bracket made of steel with Electrostatic powder coating.

Lens angle 30° - 60° - 90°

Colour standard MT-X6-23

Optional RAL codes.

LED power supply unit

Input 100 – 305V AC 50 / 60 Hz

Power factor > 90% full load

6kV surge protection

DALI controllable (optional)

0-10V / 1-10V controllable (optional)

Safety class I

Protection class IP66

Impact strenght IK09

Operation temperature -25°C / +55°C

Wind catching area: 0,32 m²

Weight: 23 kg

EULUMDAT files available

Complies with European standards

EN 60598 and CE certificate.

CE -- Conformity mark.

LAMPS

Module connected wattage	300W
Luminaire connected wattage	330W
Ambient temperature	t ^a max = 55 °C

NW

Module designation	10S109344NC-1152
Colour temperature	4000K
Colour rendering index	R ^a >80
Module luminous flux	56136 lm
Luminaire luminous flux	51084 lm
Luminaire luminous efficiency	170 lm / W

WW

Module designation	10S109344NC-1152
Colour temperature	3000K
Colour rendering index	R ^a >80
Module luminous flux	54568 lm
Luminaire luminous flux	49656 lm
Luminaire luminous efficiency	165 lm / W

Standard colour temperature 4000K

Also available with 3000K on request.

BAYLED TEKNOLOJİ A.Ş.

Ahi Evran Mah. 225. Cad. No:84

06935, Sincan ANKARA / TURKEY

T: +90 312 395 76 35

F: +90 312 395 73 65

info@bayled.com.tr

Bayled All right reserved

We reserve the right to change specifications without prior written notice.

Edition: 03.05.2016

Current version under:

www.bayled.com.tr

Bayled is a Baytaş group brand.