

# ELA 1 MODULE 30W




## URBAN LIGHTING LUMINAIRES

IP66

IK08



EN60598 CE



## PRODUCT DATA

### General Information

Number of light source	12 pcs
LED module	High Power LED's on alu-PCB
Light distribution	Asymmetric
Light source colour	3000K-4000K
Number of gear unit	1 unit
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	Multi lens
Control interface	On/Off
Connection	-
Cable	3x1,5 mm <sup>2</sup>
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Asymmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	60-74-01-30-12-XX-ASYM-X (XX:Pole height, X: Led colour)

### Operating and Electrical

Input Voltage	90-264 V AC
Input frequency	50 to 60 Hz
Inrush current	136 mA
Power factor (min.)	0.92

### Control and Dimming

Dimmable(optional)	1-10V - DALI
DMX	-

### Mechanical and Housing

Housing material	Aluminium extrusion
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	PMMA
Fixation material	Stainless steel
Mounting device	-
Effective projected area	3,00m <sup>2</sup> - 4,00m <sup>2</sup> - 5,00m <sup>2</sup> - 6,00m <sup>2</sup>
Colour	Grey
Dimensions (height x width x depth)	3000,4000,5000,6000 x 1000 x 150mm

### Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK08
Surge protection (common/differential)	6 KV/4KV

### Initial Performance (IEC Compliant)

Module luminous flux	4753 lm (4000K) / 4427 lm (3000K)
Luminaire luminous flux	4321 lm (4000K) / 4025 lm (3000K)
LED luminaire efficiency	144 lm (4000K) / 134 lm (3000K)
Colour Temperature	4000K / 3000K
	6500K also available up on request.
Colour rendering index	≥70
Rated LED power	27 W
Rated luminaire power	30 W

### Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	Variable

### Fixture Run Length

To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

