




Total Height (H1)	Head (H2)
3000mm	405mm/644mm
4000mm	405mm/644mm/885mm/1204mm
5000mm	405mm/644mm/885mm/1204mm
6000mm	405mm/644mm/885mm/1204mm
7000mm	405mm/644mm/885mm/1204mm



### PRODUCT DATA

#### General Information

Number of light source	8+8 (16 pcs)
LED module	High Power LED's on alu-PCB
Light distribution	ASYM
Light source colour	3000K-4000K
Number of gear unit	2+2
Driver / power unit	PS (Constant current)
Driver included	Yes
Optical cover / lens type	-
Control interface	On/Off
Connection	-
Cable	3x1 mm <sup>2</sup>
Protection class IEC	Safety class I
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Optic type	Asymmetric
EU RoHS compliant	Yes
Light source engine type	LED
LDT / IES photometric file	Available
Life span	Estimated average 50.000 hours
MacAdams	CCT tolerance within a 3 step MacAdams ellipse
Product code	60-74-030-02-8+8-16-XXX-XX-X (X: Led colour, XX:Lens, XXX: Pole height)

#### Operating and Electrical

Input Voltage	100-305 V AC
Input frequency	50 to 60 Hz
Inrush current	73 mA
Power factor (min.)	0.92

#### Control and Dimming

Dimmable(optional)	DALI , 1-10V
DMX	-

#### Mechanical and Housing

Housing material	Aluminium / Steel extrusion & die cast
Gasket	Silicone
Optic material	PMMA
Optical cover / lens material	Plexiglass (3mm)
Fixation material	Stainless steel
Mounting device	-
Effective projected area	0.342m <sup>2</sup> ,0.456m <sup>2</sup> ,0.57m <sup>2</sup> ,0.684m <sup>2</sup> ,0.798m <sup>2</sup>
Colour	Grey
Dimensions (height x width )	3000,4000,5000,6000,7000 mm x114 mm

#### Approval and Application

Ingress protection code	IP66
Mech. impact protection code	IK10
Surge protection (common/differential)	6KV / 4KV

#### Initial Performance (IEC Compliant)

Module luminous flux	2807 (4000K) / 2616 (3000K)
Luminaire luminous flux	8 led 8W: 1276 (4000K) / 1189 (3000K) 8 led 8W: 1276 (4000K) / 1189 (3000K)
LED luminaire efficiency	8 led 8W: 143 (4000K) / 133 (3000K) 8 led 8W: 143 (4000K) / 133 (3000K)
Colour Temperature	4000K / 3000K 6500K also available up on request.
Colour rendering index	≥70
Rated LED power	15 W
Rated luminaire power	8+8W (16 W)

#### Application Conditions

Ambient temperature range	-25°C to +55°C
Maximum dimming level	-
Net weight (piece)	Variable

