



| Total Height (H1) | Head (H2) |
|-------------------|-------------|
| 3000mm | 369mm/645mm |
| 4000mm | 369mm/645mm |
| 5000mm | 369mm/645mm |
| 6000mm | 369mm/645mm |
| 7000mm | 369mm/645mm |

PRODUCT DATA

General Information

| | |
|----------------------------|---|
| Number of light source | 80 pcs |
| LED module | High Power LED's on alu-PCB |
| Light distribution | ASYM |
| Light source colour | 3000K-4000K |
| Number of gear unit | 16 |
| Driver / power unit | PS (Constant current) |
| Driver included | Yes |
| Optical cover / lens type | - |
| Control interface | On/Off |
| Connection | - |
| Cable | 3x1 mm ² |
| Protection class IEC | Safety class I |
| CE mark | CE mark |
| ENEC mark | - |
| Warranty period | 5 years |
| Optic type | Asymmetric |
| EU RoHS compliant | Yes |
| Light source engine type | LED |
| LDT / IES photometric file | Available |
| Life span | Estimated average 50.000 hours |
| MacAdams | CCT tolerance within a 3 step MacAdams ellipse |
| Product code | 60-74-031-01-70-80-XX-X (X: Led colour , XX: Pole height) |

Operating and Electrical

| | |
|---------------------|--------------|
| Input Voltage | 100-305 V AC |
| Input frequency | 50 to 60 Hz |
| Inrush current | 318 mA |
| Power factor (min.) | 0.92 |

Control and Dimming

| | |
|--------------------|--------------|
| Dimmable(optional) | DALI , 1-10V |
| DMX | - |

Mechanical and Housing

| | |
|-------------------------------|--|
| Housing material | Aluminium / Steel extrusion & die cast |
| Gasket | Silicone |
| Optic material | PMMA |
| Optical cover / lens material | Plexiglass (3mm) |
| Fixation material | Stainless steel |
| Mounting device | - |
| Effective projected area | 0.342m ² ,0.456m ² ,0.57m ² ,0.684m ² ,0.798m ² |
| Colour | Grey |
| Dimensions (height x width) | 3000,4000,5000,6000,7000 mm x114 mm |

Approval and Application

| | |
|--|-----------|
| Ingress protection code | IP66 |
| Mech. impact protection code | IK10 |
| Surge protection (common/differential) | 6KV / 4KV |

Initial Performance (IEC Compliant)

| | |
|--------------------------|-------------------------------------|
| Module luminous flux | 11103 (4000K) / 10343 (3000K) |
| Luminaire luminous flux | 10094 (4000K) / 9403 (3000K) |
| LED luminaire efficiency | 144 (4000K) / 134 (3000K) |
| Colour Temperature | 4000K / 3000K |
| | 6500K also available up on request. |
| Colour rendering index | ≥70 |
| Rated LED power | 64 W |
| Rated luminaire power | 70 W |

Application Conditions

| | |
|---------------------------|----------------|
| Ambient temperature range | -25°C to +55°C |
| Maximum dimming level | - |
| Net weight (piece) | Variable |

Fixture Run Length To calculate fixture run lengths and total power consumption for your specific installation, please ask to company assistant

